

SAFETY DATA SHEET

SECTION 1) IDENTIFICATION

Product Name: COOLCUT SOLID
SDS No.: L-22
Product Code: 53-B 013 (300g)

Revision Date: Jun 17, 2022 **Date Printed:** Jul 08, 2022
Version: 1.0 **Supersedes Date:** N.A.

Manufacturer's Name: United States - Walter Surface Technologies Inc.
Address: 810 Day Hill Road Windsor, CT, US, 06095
Emergency Phone: INFOTRAC® 1-800-535-5053. International call collect: 1-352-323-3500 24 hours/day, 7 days/week.
Information Phone Number: +1 (866) 592-5837
Fax:
Product/Recommended Uses: Metal cutting lubricant.

SECTION 2) HAZARDS IDENTIFICATION

Type of product

Solid

Classification

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

Pictograms

None

Signal Word

Not classified

Hazardous Statements - Health

N/A

Precautionary Statements - General

Precautionary Statements - Prevention

Not applicable.

Precautionary Statements - Response

Not applicable.

Precautionary Statements - Storage

Not applicable.

Precautionary Statements - Disposal

Not applicable.

Hazards Not Otherwise Classified (HNOC)

No data available.

Hazards Not Otherwise Classified (HNOC) (Physical & Health)

no data available

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture

The product is a mixture.

The product is a pure substance.

CAS	Chemical Name	% By Weight
0064742-56-9	MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC	30.00% - 60.00%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell or are concerned.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Gently brush product off face. Do not rub eyes. Let the eyes water naturally for a few minutes. Look right and left, then up and down. If eye irritation persists: Get medical advice/attention. Do not attempt to manually remove anything from the eyes.

Skin Contact

Rinse/wash with lukewarm, gently flowing water and mild soap for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

Ingestion

If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Never give anything by mouth to an unconscious person. Rinse mouth. If you feel unwell/If concerned: Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Most important symptoms/effects, acute and delayed

Eye contact

No known significant effects or critical hazards.

Inhalation

No known significant effects or critical hazards.

Skin contact

No known significant effects or critical hazards.

Ingestion

No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact (OE)

No known significant effects or critical hazards.

Inhalation (OE)

No known significant effects or critical hazards.

Skin contact (OE)

No known significant effects or critical hazards.

Ingestion (OE)

No known significant effects or critical hazards.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Large Fire: Dry chemical, CO2, alcohol resistant foam or water spray Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Unsuitable Extinguishing Media

None. Do not use water jet.

Specific Hazards in Case of Fire

In case of fire, hazardous decomposition products may include carbon oxides. Dense smoke may be generated while burning.

Fire-fighting Procedures

Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray is recommended to cool or protect exposed materials or structures. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Isolate hazard area and keep unauthorized personnel away. Do not touch or walk through spilled material. Ventilate closed spaces before entering.

Recommended Equipment

See section 8 for specifics on protective personal equipment (PPE).

Personal Precautions

Avoid breathing dust. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Prevent further leakage or spillage if safe to do so.

Methods and Materials for Containment and Cleaning up

Stop spill/release if it can be done safely. Move containers from spill area. Dilute with water and mop up if water-soluble. Dispose of contaminated materials according to federal, state and local regulations. Pick up with inert, non-combustible material using clean, non-sparking tools and place into loosely covered plastic containers for later disposal.

SECTION 7) HANDLING AND STORAGE

General

Avoid breathing dust. Avoid contact with skin, eye or clothing. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Use good personal hygiene practices. Wash hands after use.

Ventilation Requirements

Report ventilation failures immediately. Use only with adequate ventilation to control air contaminants to their exposure limits.

Storage Room Requirements

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Keep container(s) tightly closed and properly labeled. Containers that have been opened must be carefully resealed to prevent leakage.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

If additional protection is needed for entire face, use in combination with a face shield. Wear Dust-proof goggles with side shields

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC	[(L)]; [5 (I)];	(L)			[A2]; [A4];	URT irr	[A2]; [A4];	2000

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Tables (Z1, Z2, Z3)	OSHA Skin designation	CAN_ONtmg	CAN_ONtppm
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC	500				1			

Chemical Name	CAN_ONsmg	CAN_ONsppm	NIOSH STEL (ppm)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC							

(L) - Exposure by all routes should be carefully controlled to levels as low as possible, irr - Irritation, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

9.1 Physical and Chemical Properties

Type of product : solid.

Density	8.35 lb/gal
Specific Gravity	1.00
% VOC	0.00%

Density VOC	0.00 lb/gal
Appearance	Light yellow liquid
Odor Threshold	N/A
Odour	Characteristic
pH	N/A
Water Solubility	Insoluble in the following mat
Flammability	
Flash Point Symbol	N/A
Flash Point	250.00 °C
Viscosity	Kinematic (40°C (104°F)): 0.42 cm ² /s (42 cSt)
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Initial Boiling Point and Boiling Point Range	N/A
Auto Ignition Temp	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A
Vapor Pressure	1.00 mmHg
Decomposition Pt	N/A

SECTION 10) STABILITY AND REACTIVITY

Stability

Stable under normal storage and handling conditions.

Conditions To Avoid

No data available. Avoid heat, sparks, flame, high temperature and contact with incompatible materials.

Hazardous Reactions/Polymerization

No data available.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

Based on available data, the classification criteria are not met.

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation

OVER-EXPOSURE SIGNS/SYMPTOMS: Adverse symptoms may include pain or irritation, watering, redness.

Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0064742-56-9 MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC

LD50 (oral, rodent - rat): > 5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value

LD50 (dermal, rodent - rabbit): > 5000 mg/kg, Toxic effects : Details of toxic effects not reported other than lethal dose value

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws.

SECTION 14) TRANSPORT INFORMATION

	IATA Information	IMDG Information	U.S. DOT Information	Canada TDG Information
UN number:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Proper shipping name:	N/A	N/A	N/A	N/A
Hazard class:				Not Applicable
Hazard class:	Not Applicable	Not Applicable	Not Applicable	
Packaging group:	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ):			No Data Available	
Marine Pollutant:	NA	No Data Available	No Data Available	No Data Available
Note / Special Provision:	No Data Available	No Data Available	No Data Available	No Data Available
Toxic-Inhalation Hazard:	NA	NA	No Data Available	No Data Available

SECTION 15) REGULATORY INFORMATION

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)

None of the components are listed.

Clean Air Act Section 602 Class I Substances

None of the components are listed.

Clean Air Act Section 602 Class II Substances

None of the components are listed.

DEA List I Chemicals (Precursor Chemicals)

None of the components are listed.

DEA List II Chemicals (Essential Chemicals)

None of the components are listed.

SARA 302/304

None of the components are listed.

SARA 313

None of the components are listed.

SARA 311/312

ASPIRATION HAZARD - Category 1

States regulations

Massachusetts : None of the components are listed.

New York : None of the components are listed.

New Jersey : None of the components are listed.

Pennsylvania : None of the components are listed.

Canada

Canadian NPRI : None of the components are listed.

CEPA toxic substance : None of the components are listed.

Canada inventory (DSL NDSL) : All components are listed or exempted.

International lists

Philippines : All components are listed or exempted.

Taiwan : All components are listed or exempted.

China : All components are listed or exempted.

New Zealand : All components are listed or exempted.

Turkey : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Europe : All components are listed or exempted.

Australia : All components are listed or exempted.

California Proposition 65

Prop 65: No products found

CAS	Chemical Name	% By Weight	Regulation List
0064742-56-9	MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC	30% - 60%	DSL,SARA312,TSCA

Product does not contain any chemicals listed under California Proposition 65

SECTION 16) OTHER INFORMATION

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.