

## BOLT-OUT™

### DESCRIPTION

Bolt –Out™ is a premium penetrating lubricant which is a heavy-duty, non chlorinated formula that initially penetrates and then lubricates seized parts while inhibiting further rust in a wide range of temperatures.

Its Microscopic ‘Moly’ particles provide excellent lubrication and protection. Bolt-Out™ has the following benefits:

- It displaces moisture
- It is silicone free
- Approved for use in food plants
- Contains no CFC, HCFC or chlorinated solvents.
- Faster disassembly with less effort
- Non flammable liquid

### APPLICATIONS

Bolt-Out™ can be used in industries as well as workshops. It is effective in a wide range of temperature (-20°C to 250°C). It is created for:

- Disassembly of seized bolts, nuts, mechanisms, pins bushing, etc.
- Loosening of hoists, pulley blocks, hinges.
- Eliminating squeaking noise from moving parts.
- Maintenance, repair, overhaul, re-building.
- Plant shut-downs and fleet maintenance

### DIRECTIONS FOR USE

Shake can very well before use. Remove loose rust and excess dirt. Spray on seized parts and allow time for penetration before disassembling.

### TECHNICAL DATA

**Physical state:** Aerosol

**Colour:** Dark gray

**Density:** 0.791 g/mL (20°C/ 68°F)

**VOC:** 98.5% (w/w)

**Flash point:** -60°C (-76°F)

**Working temperature:** Effective from -20°C to 250°C (-5°F to 485°F)

**Engineering controls:** Ensure adequate ventilation.

**Incompatible substances:** Strong oxidizing agents.

**Storage:** Store below 50°C/122°F.

**Shelf life:** 2 years in closed container, stored in ideal conditions.

### ORDERING INFORMATION

| Description     | Size  | Order No. | (M)SDS |
|-----------------|-------|-----------|--------|
| Aerosol         | 400mL | 53-D892   | L-08E  |
| Sprayer Trigger | 500mL | 53-D893   | L-26E  |
| Liquid          | 20L   | 53-D897   | L-26E  |

(M) SDS available upon request or visit our web site at [www.walter.com](http://www.walter.com)

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.

Walter Surface Technologies Inc.

5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1

Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825