

FOOD ZONE

Food grade general purpose lubricant

Multi-purpose lubricant and penetrating oil for food industry plants.

Features & benefits

- NSF approved H1 FOOD GRADE LUBRICANT for incidental contact with food
- Excellent and fast penetration of rust, scale and general dirt and grime, to loosen seized and rusted parts
- Displaces water and moisture
- Leaves a thin protective film
- Non-conductive
- Water resistant
- Resists chemical attack
- Temperature range: -10°C /14°F to 180°C/356°F
- CO2 non flammable propellant

| DESCRIPTION | SIZE | ORDER NO. | SDS |
|-------------|------------------|-----------|-------|
| Aerosol | 400 ml / 13.5 oz | 53 D 602 | L-153 |

Remove with:

Slap Shot aerosol, 500ml 53-C 502
Slap Shot sprayer, 500ml 53-C 503
Slap Shot, 5L 53-C 506
Slap Shot, 20L 53-C 507
Slap Shot, 200L 53-C 508
Slap Shot PL aerosol, 500ml 53-C 552

Technical information

| | |
|---------------------|----------------------------------|
| Density@20°C (68°F) | 1.19g/cm ³ |
| Flash Point | 62°C /144°F |
| Odor/color | Mild/yellow |
| Dielectric Strength | Non conductive |
| Solubility in water | Not miscible or difficult to mix |
| Viscosity | N/D |