

# HANG ON™

## DESCRIPTION

HANG-ON™ is a very tenacious maintenance lubricant that adheres remarkably to all metallic surfaces, providing efficient and long lasting lubrication and protection, even in harsh environments and under load. Surpasses and lasts longer than all-purpose and standard thin film lubricants.

## FEATURES

- Penetrates and adheres to metallic surfaces to ensure a durable lubrication.
- Long lasting protection against corrosion.
- Displaces moisture inside mechanisms. Repels water.
- Resists to high loads, bad weather, salt water and aqueous chemicals.
- Clean film. Does not drip or stain.
- Can be applied on moving equipment.
- Reduces downtimes and maintenance frequency.
- Economical due to its efficient and long lasting action.

## APPLICATIONS

Joints and couplings, runners, hinges, fork lifts, all mechanisms with mobile parts, as well as locks, chains, cables, rods and gears.

## APPROVALS

Approved by CFIA for food industries. Avoid contamination of food during the use and storage of this product.

## COMPATIBILITY OF MATERIALS\*

**Excellent** : Ferrous metals, non-ferrous metals, Nitrile (Buna), carbon graphite, LDPE, Nylon, PVC, Viton.

**Non-compatible** : ABS, EPDM, Neoprene, natural rubber.

\* For reference only. The results may vary according to conditions. Always test compatibility before using on materials other than metals.

## TECHNICAL INFORMATION

**Physical state**: Viscous clear liquid, dries as an oily viscous clear film.

**Color**: Yellow

**Density**: 0.73 g/ml (20°C / 68°F)

**VOC**: 73.7% (w/w)

**Flash point**: -60°C (-76°F)

**Working temperature**: Effective from -35°C to 200°C (-31°F to 392°F)

**Engineering controls**: Ensure good ventilation, do not expose to very high temperatures or sources of ignition

**Incompatible substances**: strong oxidants

**Shelf life**: 2 years in closed container, stored in ideal conditions

**Storage**: under 50°C (120°F)

**Cleaning**: Use a solvent (Walter Slap Shot™ 53-C 502) or a water-based cleaner/degreaser (Walter UNO S F™ 53-G 023)

## INFORMATION TO ORDER

Description	Size	Order No.	(M)SDS
Aerosol	400ml	53-D 812	L-33F
Liquid	20 L	53-D 817	L-45F

### Accessories

Refillable trigger sprayer

500ml 53-L 331

Spout for metal containers

20 L round 53-L 211

(M) SDS available upon request or visit our web site at [www.walter.com](http://www.walter.com)

Not for product specification. The technical data contained herein is intended as reference only and may change without notice.