

SLAP SHOT™

DESCRIPTION

A rapid-evaporating, fast acting cleaner/degreaser, that completely dissolves and washes off stubborn dirt and grease without leaving a residue. Displaces moisture and prepares surfaces for subsequent treatment such as painting or re-lubrication. For use when an ultra clean surface is required and as a high performance alternative to 1,1,1-trichloroethylene.

- Get the job done in one operation.
- Prepares surfaces for painting or re-lubrication.
- Chlorinated solvent free.
- No rinsing, no residue.
- Fast evaporation.
- Safe on all metals.
- Aerosol jet with strong jet to blast away tough grime.
- Dissolves grease and oil quickly and completely.
- Displaces moisture.

APPLICATIONS

Contaminants:

Removes oil, grease, paint, ink, glue, adhesive, wax and rubber.

Surfaces:

All metals. For example machine parts, engines, gears, cables, chains, forklifts, cranes, pumps and industrial equipment.

Directions for Use:

Shake well before use. Spray or apply onto soiled surfaces.

TECHNICAL DATA

Appearance : Clear liquid, kerosene odour

Flash point (°C): - 60 (aerosol) or -24 (liquid)

Boiling point (°C): Above 60 (liquid)

Melting point (°C): <-30 (for the liquid)

Vapour pressure (@ 20°C): 4500 hPa (aerosol) or 200 hPa (liquid)

Density (@ 20°C): 0.73 g/ml(aerosol) or 0.78 g/ml(liquid)

Solubility in water : Not miscible

PH :N/A

Viscosity(@ 20°C): N/A(aerosol) or <10 nPa.s(liquid)

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	MSDS
Aerosol		500 ml	53-C 502
L-39E			
Sprayer		500ml	53-C 503
L-40E			
Liquid	5 L	53-C 506	L-40E
Liquid	20 L	53-C 507	L-40E
Liquid	200 L	53-C 508	L-40E

Accessories

Replacement trigger bottle	53-L 311
Transfer valve 5L	53-L 102
Transfer valve 20L	53-L 102
Transfer valve 200L	53-L 208