


# SURFOX-T

## Heavy-Duty Electrolyte Cleaning Solution

SURFOX-T is a heavy-duty electrolyte cleaning solution that removes weld discoloration and enhances passivation to the work surface without the use of dangerous pickling paste. With the combination of Surfox-T and our Surfox accessories, weld discoloration of TIG, MIG, and SPOT welds will be removed instantly and the original finish will be restored, requiring no further treatment.



### Features & benefits:

- Highly effective electrolyte cleaning solution
- No scrubbing or mechanical action required
- Instant cleaning of heat tint from welding
- Non-flammable, VOC free
- **The use of SURFOX systems is a recognized method for achieving chemical passivation on Stainless Steel Parts, as defined by the ASTM A967 specification;**
- NSF registered under category code A3, registration No. 142984
- **TIP:** Neutralize with SURFOX-N to complete the cleaning process



| Description | Size (metric) | Size (Imperial) | Order No. | SDS   |
|-------------|---------------|-----------------|-----------|-------|
| Liquid      | 100 ml        | 3.4 oz          | 54-A 001  | S-01E |
| Sprayer     | 1.5 L         | 51 oz           | 54-A 005  | S-01E |
| Liquid      | 5 L           | 1.3 gal         | 54-A 006  | S-01E |
| Liquid      | 20 L          | 5.2 gal         | 54-A 007  | S-01E |
| Liquid      | 208 L         | 55 gal          | 54-A 008  | S-01E |

### ACCESSORIES

|                  |          |
|------------------|----------|
| SURFOX-N, 500 ml | 54-A 023 |
| SURFOX-N, 5 L    | 54-A 026 |
| SURFOX-N, 20 L   | 54-A 027 |
| SURFOX-N, 208 L  | 54-A 028 |
| MINI-SURFOX      | 54-D 054 |
| SURFOX 205       | 54-D 215 |
| SURFOX 304       | 54-D 314 |

### Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Density                     | 1.38 g/ml @ 20°C    |
| Flashpoint                  | N/A                 |
| Odor/color                  | Acidic, Clear       |
| pH (50g/L H <sub>2</sub> O) | <1                  |
| Rinsability                 | Miscible with water |
| VOC                         | 0                   |

SDS available upon request or on our website at [www.walter.com](http://www.walter.com) | [www.surfox.com](http://www.surfox.com)

Walter Surface Technologies Inc.

5977 Trans-Canada Highway, Pointe-Claire, Quebec H9R 1C1

Tel: 1-800-592-5837 or (514)630-2800 / Fax: (514)630-2825 / Web: [www.walter.com](http://www.walter.com)