

UNO S™

Concentrated Cleaner and Degreaser

UNO S™ is an aqueous based high strength degreaser which uses advanced cleaning technology to deliver outstanding performance. The excellent dissolving property of UNO S™ allows the product to achieve optimal results at ambient temperature. The foaming action of UNO S™ makes this product ideal for increased contact time and manual cleaning applications.

Features & Benefits:

- High strength concentrate, economical to use
- Can be diluted up to 1:50 to suit all cleaning needs
- Removes oil, grease, grime, carbon deposits, markers, smoke residue, organic contaminants, dust, etc.
- Achieves optimal results at ambient temperature
- For manual use (trigger sprayer)
- Built in corrosion inhibitors to prevent flash rusting
- Water-based, non-flammable
- Biodegradable, VOC free
- Solvent, phosphate and butyl-free
- **UNO S™** is a foaming formulation
- Also available in a foamless formulation (**UNO S F™**)



Description	Size		Order No.	(M)SDS
	Metric	Imperial		
Trigger sprayer	500ml	16.9 fl. oz.	53-G 033	L-143E
Liquid	3.78L	1 gal.	53-G 036	L-143E
Liquid	20L	5.2 gal.	53-G 037	L-143E
Liquid	208L	55 gal.	53-G 038	L-143E
Liquid	1000L	264 gal.	53-G 039	L-143E

ACCESSORIES

Spout for 5L pail	53-L 113
Spout for 20L pail	53-L 207
Faucet for 208L drum, 2"	53-L 209
Faucet for 208L drum, ¾"	53-L 210
Replacement trigger sprayer 500 ml	53-L 335

Technical Information

Density	1.04 g/ml (at 68°F)
Flashpoint	N/A
Odor/color	Mild odor/ light pink
pH (at 100g/L H₂O)	12.5
Rinsability	Excellent
VOC	0% wt

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice

UNO S™

Concentrated Cleaner and Degreaser

Application Chart:

Equipment	Dilution ratio	Dilution %	Application	Material
Trigger sprayers	1:50 - 1:30	2,0% - 3,3%	Removal of light organic contaminants	Aluminum, Non-Ferrous Alloys, Zinc Coatings, Plastics
Trigger sprayers	1:50 - 1:10	2,0% - 10%	Removal of light organic contaminants	Steel, Stainless Steel, Plastic
Trigger sprayers	1:10 - Pure	10% - Pure	Removal of heavy organic contaminants	Steel, Stainless Steel

Dilution Chart

Dilution ratio	Dilution %	ml of cleaner/ 1L of water	fl. oz. of cleaner/ 1 gal of water
1:50	2	20 ml	0, 68 fl. Oz.
1:40	2,5%	25ml	3,2 fl. Oz.
1:30	3,3%	33ml	4,3 fl. Oz.
1:20	5%	50ml	6,4 fl. Oz.
1:10	10%	100ml	12,8 fl. oz.
1:5	20%	200ml	25,6 fl. oz.
1:2	50%	500ml	64 fl. oz.

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice